

SPOT WELDING MACHINE TM-333



OVERVIEW

TM-333 Spot Welding Machine is compact, easy to operate and provide fast and effective means for spot welding thin or fine metal to other metal wire or sheet plate. The integrated TAB switch offers selection of current pulse according to different welding applications. The flow of electric current to the weld head can be manually activated by foot switch, hence facilitating easy operation.

SPOT WELDING MACHINE TM-333

FEATURES & BENEFITS

- Interchangeable copper electrode
- TAB switch provides selection of current pulse
- Single phase resistance weld type
- Indication of firing signal
- Weld head is manually operated by foot switch
- User-friendly programme interface
- Password protection

APPLICATIONS

- Sheet plate welding
- Wire to metal welding
- Suitable for materials like invar, stainless steel, M.S etc

SPECIFICATIONS

Power Requirement	230VAC 10%
Operating Temperature	18°C to 28°C
Max. Rated Power	5KVA
Selectable Voltage (Output)	1V, 1.6V, 2.5V, 4V
Max. Welding Current	1000 amps
Max. Welding Voltage	4V
Dimension	440mm (L) x 390mm (W) x 380mm (H)
Weight	25kg

Specifications are subjected to change without prior notice

HEADQUARTER (SINGAPORE)



TRIMECH TECHNOLOGY PTE LTD

A member of TRIMECH group of companies
No. 70 Ubi Crescent #01-02/03

Ubi Techpark
Singapore 408570

Tel : 65 6741 0346

Fax: 65 6741 7850

Email: sales@cherusal.com

Website: www.cherusal.com



Certificate No: 651176

REGIONAL OFFICES

• Beijing

Tel: (86) 10 6566 2172
Fax: (86) 10 6566 2171
Email: james-zj_yao@cherusal.com

• Hong Kong

Tel: (852) 2111 0982
Fax: (852) 2111 0983
Email: bs_tan@cherusal.com

• Shenzhen

Tel: (86) 755 8231 8767
Fax: (86) 755 8231 8763
Email: bs_tan@cherusal.com

• Shanghai

Tel: (86) 21 5055 1008 ext 16
Fax: (86) 21 5834 6323
Email: james-zj_yao@cherusal.com

• Taiwan

Tel: (886) 3 262 1188
Fax: (886) 3 262 0208
Email: kenny-tan@cherusal.com

• Thailand

Tel : (66) 2 690 2466
Fax : (66) 2 690 2467
Email: nipon_k@cherusal.com